

GENERAL

STONE INSTALLATION INSTRUCTIONS

ErthCOVERINGS® recommends that all natural stone products that are not polished and are being grouted should be sealed to prevent grout stains and to make the removal of grout haze much easier. Failure to seal an un-polished surface prior to grouting could result in dis-colouration of the stone surface that cannot be corrected.

Please refer to the table below to determine the suitable sealers, grout, and installation method for your stone. A test sample may be needed prior to installation to confirm the desired look can be achieved.

	CAN BE GROUTED	MUST BE GROUTED	UNSANDED GROUT ONLY	CAN BE SEALED	MUST BE SEALED	NATURAL LOOK SEALER ONLY	
STONE COVERINGS	3D Series (ALL)						Panel Installation Instructions
	Ledgestone (ALL)						Panel Installation Instructions
	Rough Break (ALL)						Panel Installation Instructions
	Splitface (ALL)						Splitface Installation Instructions
	Strips (ALL)						Strips Installation Instructions
	Cascade (ALL)						Panel Installation Instructions
	HandiPak (ALL)						HandiPak Installation Instructions
	Pebbles (ALL)						Pebbles Installation Instructions
	ILPM Slate (ALL)						ILPM Installation Instructions
	Planks (ALL)						Planks Installation Instructions
STONE TILES	Bailey						Tile Installation Instructions
	Black Pearl						Tile Installation Instructions
	Bliss Honed						Tile Installation Instructions
	Bliss Polished						Tile Installation Instructions
	Flare Honed						Tile Installation Instructions
	Flare Polished						Tile Installation Instructions
	Lavastone						Lavastone Installation Instructions
	Seville						Tile Installation Instructions
	Tivoli						Tile Installation Instructions
	Vienna						Tile Installation Instructions